



고압증기멸균기

AUTOCLAVE

How It Works

Only a solidly and sturdily designed chamber and lid can keep the high pressure safely. When the temperature goes up and the chamber limits its space, only the pressure will go stronger. This process makes higher than 110 °C of steam in the chamber.

The Purpose of Use

Not all living organisms badly suffer from 110 °C of heat. Some living organisms are able to resist heat due to their structural protein walls. However, any micro-organism cannot survive from over 121 °C of steam. Therefore, the design purpose of Autoclave is to ensure a sterile environment in each field of life and science.

The Field of Use

Bio and life science laboratory, medical institution, food production industry, veterinary industry, and etc.

Autoclave



SJ-FW
45/60/80/100



SJ-FW series shows how we make difference among many steam sterilizers. SJ-FW can efficiently locate in various sizes of laboratories. The well-arranged design and fully automatic system must bring more space and save time.

- Fully Automatic Process** Water Supply > Heating > Exhaust Residual Air > Sterilization > Steam Vent > Complete
- Efficient Design** The front focused controller allows the compact size and the efficient space arrangement
- Long Term Use** The heart of the autoclave (chamber& heater) is well protected and prepared for low maintenance (CE PED / Automatic Water Supply / Stainless Steel 304)
- P.I.D Control & Auto-Tuning** Precise temperature control by P.I.D and smart work efficiency with auto-tuning function

Safety Device

1. Over-temp Prevention
2. Over-pressure Prevention
3. Manual Steam Valve
4. Steam Cooling Discharge Method
5. Circuit Breaker
6. Water Level Sensor



Door



Water Inlet



Water Level Indicator



Controller



Pressure Gauge



Manual Steam Valve



Steam Outlet



Recorder (Options)

SJ-FW series Specifications



For product improvement, the specification below is subject to change without prior notice. Please, contact us for the specification consultant.

Spec / Model		SJ-FW45	SJ-FW60	SJ-FW80	SJ-FW100
Type		Fully Automatic Type			
Chamber Type		Round Vertical Type			
Capacity		45ℓ	62ℓ	81ℓ	103ℓ
In Size (ØxH)m/m		300x650	350x650	400x650	450x650
Dimension (WxDxH)m/m		600x610x1,100 (About)	600x610x1,100 (About)	675x690x1,160 (About)	675x690x1,160 (About)
Heater Capacity		2kw	3kw	4kw	4kw
Temp.	Range	Ambient to 130℃			
	Controller	FND & LED Microprocessor Programmable Control			
	Sensor	Pt-100Ω (Exclusively for Sterilizing, Auto Tuning)			
Time Range		99Hours 59min Digital Display			
Accuracy		±0.5℃			
Material	IN	Stainless Steel 304			
	OUT	SS41 Steel Plate and Powder Coating			
Door System		One Handle Type (Single Screw)			
Basket		Stainless Steel (#304) Manufactured for Sterilizing / 2ea			
Pressure Range		0~3kg/cm ²			
Using Pressure		0~1.2kg/cm ²			
Wheel		Retractable Leveling Caster			
Electronic Power		AC 220V, 50-60Hz Single-Phase			
Safety Device		Safety Pressure Valve / Over Temp. Protection / Over Pressure Protection / Manual Steam Valve / Steam Cooling Discharge Method / Circuit Breaker / Water Level Sensor / Buzzer Alarm / etc.			

ЛАБОРАТОРНОЕ ОБОРУДОВАНИЕ ■ ПЛАСТИК ■ СТЕКЛО ■ РЕАКТИВЫ ■ НАБОРЫ

www.dia-m.ru
заказ онлайн